



**MCR
SAFETY**

B3N FR Gear Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The B3N Insulated Bomber Jacket features a comfortable 88% Cotton 12% Nylon material with a modacrylic quilted lining for warmth and protection. Max Comfort™ material meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular and Tall Sizing, Navy



FEATURES:

- Max Comfort™ Fabric NFPA 2112 UL Certified
- All Trims are NFPA 2112 UL Certified
- NFPA 70E Hazard/Risk Category 3 (HRC3), Arc Flash PPE Category 3 (CAT3)
- ASTM F1506 Electric Arc Protection Standard
- ATPV ASTM 1959 35 cal/cm², HRC3/CAT3
- Bomber Jacket is UL & NFPA 2112 Certified
- **Max Comfort™ 7.5 oz. 88% Cotton/12% Nylon Outer Shell**
- **11.5 oz. quilted lining – 100% FR treated cotton and non-woven modacrylic batting**
- Water Repellent
- Sewn with FR Aramid thread
- Double needle stitching and tacking for reinforcement
- 2 Inset Hand pockets
- Pleated action back provides arms with 360 degree full range of motion
- FR Brass #10-Nomex 1-way separating front zipper closure with protective storm flap with snap closure
- Knit cuffs and waistband

APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking, Mining

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

B3N
FR Gear
Specification Sheet

TECHNICAL DATA FOR: B3N

Series	Max Comfort	Front Closure	YKK 2-Way Zipper & Snaps
Category	FR Gear	NFPA 2112 Cert.	Yes
Size	Large	NFPA 70E Cert.	Yes
Material	Flame Resistant, 88% Cotton / 12% Nylon - Max Comf	ASTM 1930 Cert.	Yes
Material Weight	7.5 oz.	ASTM F1506 Cert.	Yes
Flame Resistant	Flame Resistant	Hazard Risk Category	HRC3

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
B3NS	36-38	N/A	N/A	N/A	N/A	N/A	26.512
B3NM	40-42	N/A	N/A	N/A	N/A	N/A	28.032
B3NLT	44-46	N/A	N/A	N/A	N/A	N/A	31.800
B3NL	44-46	N/A	N/A	N/A	N/A	N/A	29.592
B3NXLT	48-50	N/A	N/A	N/A	N/A	N/A	33.144
B3NXL	48-50	N/A	N/A	N/A	N/A	N/A	30.664
B3NX2	52-54	N/A	N/A	N/A	N/A	N/A	32.040
B3NX2T	52-54	N/A	N/A	N/A	N/A	N/A	33.624
B3NX3	56-58	N/A	N/A	N/A	N/A	N/A	33.624
B3NX3T	56-58	N/A	N/A	N/A	N/A	N/A	34.448
B3NX4T	60-62	N/A	N/A	N/A	N/A	N/A	36.920
B3NX4	60-62	N/A	N/A	N/A	N/A	N/A	37.760
B3NX5T	64-66	N/A	N/A	N/A	N/A	N/A	38.248
B3NX5	64-66	N/A	N/A	N/A	N/A	N/A	37.040

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved