



**MCR
SAFETY**

CC2N

Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The CC2 Coverall features a comfortable 100% cotton material that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular and Tall Sizing, Navy and Tan

Sizes available: 34-66



FEATURES:

- **Available in Regular and Tall Sizing, Navy and Tan**
- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- NFPA 70E Hazard/Risk Cat HRC2/ATPV ASTM 1959 9.6 cal/cm²
- Max Comfort™ 7 oz. 100% cotton FR twill fabric
- Two-way concealed Nomex FR brass break-away zipper
- One patch pocket on chest
- Side vent pass throughs
- Five-thread overlock stitching
- Two front pockets and two rear patch pockets on coverall pants
- Sewn with Nomex FR thread
- One piece, top stitched, lay flat collar

APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking, Mining

TECHNICAL DATA FOR: CC2N

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

CC2N

Specification Sheet

Series	Max Comfort	Front Closure	YKK 2-Way Zipper & Double
Material Weight	7.0 oz.		Snap
Flame Resistant	Flame Resistant	NFPA 2112 Cert.	Yes
		NFPA 70E Cert.	Yes
		ASTM 1930 Cert.	Yes
		ASTM F1506 Cert.	Yes
		Hazard Risk Category	HRC2

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
CC2N34	34	N/A	N/A	N/A	30	N/A	16.990
CC2N36	36	N/A	N/A	N/A	30	N/A	17.830
CC2N36T	36	N/A	N/A	N/A	32	N/A	18.440
CC2N38	38	N/A	N/A	N/A	30	N/A	18.270
CC2N38T	38	N/A	N/A	N/A	32	N/A	19.160
CC2N40T	40	N/A	N/A	N/A	32	N/A	19.710
CC2N42	42	N/A	N/A	N/A	30	N/A	18.464
CC2N42T	42	N/A	N/A	N/A	32	N/A	20.100
CC2N46T	46	N/A	N/A	N/A	32	N/A	21.585
CC2N46	46	N/A	N/A	N/A	30	N/A	20.320
CC2N48	48	N/A	N/A	N/A	30	N/A	20.784
CC2N48T	48	N/A	N/A	N/A	32	N/A	25.700
CC2N50T	50	N/A	N/A	N/A	32	N/A	25.700
CC2N50	50	N/A	N/A	N/A	30	N/A	21.770
CC2N52T	52	N/A	N/A	N/A	32	N/A	23.310
CC2N52	52	N/A	N/A	N/A	30	N/A	22.010
CC2N54	54	N/A	N/A	N/A	30	N/A	23.640
CC2N54T	54	N/A	N/A	N/A	32	N/A	24.070
CC2N56T	56	N/A	N/A	N/A	32	N/A	24.770
CC2N58T	58	N/A	N/A	N/A	32	N/A	25.500
CC2N58	58	N/A	N/A	N/A	30	N/A	24.310
CC2N60T	60	N/A	N/A	N/A	32	N/A	25.890
CC2N62T	62	N/A	N/A	N/A	32	N/A	26.790
CC2N64T	64	N/A	N/A	N/A	32	N/A	27.290
CC2N66T	66	N/A	N/A	N/A	32	N/A	27.990

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved