



**MCR
SAFETY**

CC2T

Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The CC2 Coverall features a comfortable 100% cotton material that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee. **Available in Regular and Tall Sizing, Navy and Tan**



FEATURES:

- Available in Regular and Tall Sizing, Navy and Tan
- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- NFPA 70E Hazard/Risk Category 2 (HRC2), Arc Flash PPE Category 2 (CAT2)
- ASTM 1959 9.6 cal/cm²
- Max Comfort™ 7 oz. 100% cotton FR twill fabric
- Two-way concealed Nomex FR brass break-away zipper
- One patch pocket on chest
- Side vent pass throughs
- Five-thread overlock stitching
- Two front pockets and two rear patch pockets on coverall pants
- Sewn with Nomex FR thread
- One piece, top stitched, lay flat collar

APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking, Mining

TECHNICAL DATA FOR: CC2T

Series	Max Comfort	Front Closure	YKK 2-Way Zipper & Double Snap
Material Weight	7.0 oz.	NFPA 2112 Cert.	Yes
Flame Resistant	Flame Resistant		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved



MCR
SAFETY

CC2T

Specification Sheet

NFPA 70E Cert. Yes
 ASTM 1930 Cert. Yes
 ASTM F1506 Cert. Yes
 Hazard Risk Category HRC2

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
CC2T34	34	N/A	N/A	N/A	30	N/A	16.210
CC2T36T	36	N/A	N/A	N/A	32	N/A	17.690
CC2T38	38	N/A	N/A	N/A	30	N/A	17.890
CC2T38T	38	N/A	N/A	N/A	32	N/A	18.110
CC2T40T	40	N/A	N/A	N/A	32	N/A	18.390
CC2T40	40	N/A	N/A	N/A	30	N/A	18.360
CC2T42	42	N/A	N/A	N/A	30	N/A	19.030
CC2T42T	42	N/A	N/A	N/A	32	N/A	19.230
CC2T46T	46	N/A	N/A	N/A	32	N/A	20.280
CC2T48T	48	N/A	N/A	N/A	32	N/A	20.750
CC2T48	48	N/A	N/A	N/A	30	N/A	20.490
CC2T50T	50	N/A	N/A	N/A	32	N/A	21.320
CC2T50	50	N/A	N/A	N/A	30	N/A	21.110
CC2T52	52	N/A	N/A	N/A	30	N/A	21.750
CC2T52T	52	N/A	N/A	N/A	32	N/A	21.920
CC2T54T	54	N/A	N/A	N/A	32	N/A	22.540
CC2T56T	56	N/A	N/A	N/A	32	N/A	23.050
CC2T56	56	N/A	N/A	N/A	30	N/A	23.100
CC2T58T	58	N/A	N/A	N/A	32	N/A	23.920
CC2T58	58	N/A	N/A	N/A	30	N/A	23.350
CC2T60T	60	N/A	N/A	N/A	32	N/A	24.350
CC2T60	60	N/A	N/A	N/A	30	N/A	23.930
CC2T62T	62	N/A	N/A	N/A	32	N/A	25.080
CC2T64T	64	N/A	N/A	N/A	32	N/A	25.700
CC2T66T	66	N/A	N/A	N/A	32	N/A	26.360

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved