



**MCR
SAFETY**

**DC3N
FR Gear**

Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The DC3N coveralls feature a comfortable 88% cotton 12% Nylon twill material that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. It also features a modacrylic quilted lining for warmth and protection. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular or Tall Sizes, Navy



FEATURES:

- Max Comfort™ Fabric NFPA 2112 UL Certified
- All Trims are NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection Standard
- NFPA 70E Hazard, HRC 3
- ATPV ASTM 1959 35 cal/cm², HRC 3
- Coverall is UL & NFPA 2112 Certified
- Max Comfort™ 7.5 oz. 88% Cotton/12% Nylon Outer Shell
- 11.5 oz. quilted lining – 100% FR treated cotton and non-woven modacrylic batting
- Water Repellent
- Sewn with FR Aramid thread
- Double needle construction on main seams
- Two patch pockets on chest with snap closure
- Two back patch pockets with concealed snap closures
- Protective storm flap covers 2-way #10 brass non-separating front zipper
- FR knit cuffs inside sleeve for better warmth and comfort
- Pleated action back provides arms with 360 degree full range of motion
- Vented legs w/10m FR zipper closure 28". The zipper is protected by storm flaps with snap closures
- Side pass through with snap closures
- Right Leg utility pocket
- Two-piece insulated stand-up collar with concealed snap closure
- Full back elastic in waistband

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

DC3N
FR Gear
Specification Sheet

■ Pen pocket on left sleeve

APPLICATIONS:

Oil and Gas Industry, Electronic Assembly, Fracking, Mining,
Utilities

TECHNICAL DATA FOR: DC3N

Series	Max Comfort	Front Closure	Triple Snap & Zipper
Category	FR Gear	NFPA 2112 Cert.	Yes
Size	Large	NFPA 70E Cert.	Yes
Material	Flame Resistant, 88% Cotton / 12% Nylon - Max Comf	ASTM 1930 Cert.	Yes
Material Weight	7.5 oz.	ASTM F1506 Cert.	Yes
Flame Resistant	Flame Resistant	Hazard Risk Category	HRC3

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC3NS	36-38	N/A	N/A	N/A	30	N/A	23.552
DC3NM	40-42	N/A	N/A	N/A	30	N/A	24.420
DC3NLT	44-46	N/A	N/A	N/A	32	N/A	26.312
DC3NL	44-46	N/A	N/A	N/A	30	N/A	25.380
DC3NXL	48-50	N/A	N/A	N/A	30	N/A	26.680
DC3NXLT	48-50	N/A	N/A	N/A	32	N/A	27.320
DC3NX2T	52-54	N/A	N/A	N/A	32	N/A	41.890
DC3NX2	52-54	N/A	N/A	N/A	30	N/A	27.740
DC3NX3	56-58	N/A	N/A	N/A	30	N/A	29.600
DC3NX3T	56-58	N/A	N/A	N/A	32	N/A	29.592
DC3NX4T	60-62	N/A	N/A	N/A	32	N/A	31.212
DC3NX4	60-62	N/A	N/A	N/A	30	N/A	30.960
DC3NX5T	64-66	N/A	N/A	N/A	32	N/A	32.660
DC3NX5	64-66	N/A	N/A	N/A	30	N/A	34.532

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved