



**MCR
SAFETY**

DC4B

Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The DC4 coveralls feature a comfortable 88% cotton 12% Nylon twill material that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. It also features FR Reflective Material for Hi-Visibility in low light areas. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular or Tall Sizes, Royal Blue



FEATURES:

- ASTM F1506-08 Electric Arc Protection Standard
- NFPA 70E-2012 Hazard/ Risk Category HRC2
- ATPV ASTM 1959 11.7 cal/cm², HRC 2
- CAN/CGSB155.20-2000
- CAN/CGSB155.22-97, OSHA 29 CFR 1910.269
- CAN/CSA Z96-09 CLASS 1/LEVEL FR
- GARMENT IS UL CERTIFIED TO CANADIAN STANDARDS
- **Max Comfort™ 9 oz. 88% Cotton/12% Nylon FR twill fabric**
- Two patch pockets on chest with snap closure
- Two-way concealed 5M -2- way nomex FR brass break-away zipper
- Two front set-in hip pockets
- Side vent pass throughs
- Two back patch pockets with concealed snap closures
- Bi-swing back for ease of movement and comfort
- Vented adjustable cuff with interior fabric coverage, complete comfort with no exposure
- One-piece, topstitched, lay flat collar
- Sewn with FR Aramid thread
- FR yellow-silver-yellow reflective tape: arms, legs, complete stripes on front
- FR yellow-silver-yellow reflective tape: X on back with complete belt
- Pen pocket on left sleeve

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

DC4B

Specification Sheet

APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking,
Mining

TECHNICAL DATA FOR: DC4B

Series	Max Comfort	Front Closure	YKK 2-Way Zipper & Triple Snap
Material	Flame Resistant, 88% Cotton / 12% Nylon - Max Comf	NFPA 2112 Cert.	Yes
Material Weight	9.0 oz.	NFPA 70E Cert.	Yes
Flame Resistant	Flame Resistant	OSHA 29 CFR 1910.269	Yes
		CAN/CGSB 155.20-2000	Yes
		CAN/CGSB 155.22-97	Yes
		CAN-CSA Z96-09 CLASS 1/LE	Yes
		ASTM 1930 Cert.	Yes
		ASTM F1506 Cert.	Yes
		Hazard Risk Category	HRC2

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC4B60T	N/A	N/A	N/A	N/A	N/A	N/A	49.944
DC4B40T	N/A	N/A	N/A	N/A	N/A	N/A	37.896
DC4B52T	N/A	N/A	N/A	N/A	N/A	N/A	31.060
DC4B44T	N/A	N/A	N/A	N/A	N/A	N/A	40.536
DC4B42	N/A	N/A	N/A	N/A	N/A	N/A	39.816
DC4B46T	N/A	N/A	N/A	N/A	N/A	N/A	31.060
DC4B48T	N/A	N/A	N/A	N/A	N/A	N/A	31.060
DC4B56T	N/A	N/A	N/A	N/A	N/A	N/A	41.352
DC4B38	N/A	N/A	N/A	N/A	N/A	N/A	36.636
DC4B54T	N/A	N/A	N/A	N/A	N/A	N/A	46.596
DC4B60	N/A	N/A	N/A	N/A	N/A	N/A	51.336
DC4B46	N/A	N/A	N/A	N/A	N/A	N/A	41.724
DC4B58T	N/A	N/A	N/A	N/A	N/A	N/A	48.780
DC4B54	N/A	N/A	N/A	N/A	N/A	N/A	47.784
DC4B50T	N/A	N/A	N/A	N/A	N/A	N/A	43.236
DC4B42T	N/A	N/A	N/A	N/A	N/A	N/A	39.684
DC4B34	N/A	N/A	N/A	N/A	N/A	N/A	31.060
DC4B40	N/A	N/A	N/A	N/A	N/A	N/A	38.904