



**MCR
SAFETY**

DC5B FR Gear

Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The DC5B coveralls feature a comfortable 88% cotton 12% Nylon twill material that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. They also feature a modacrylic quilted lining for protection and warmth and a wind and vapor barrier for outstanding comfort. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.



FEATURES:

- ASTM F1506-08 Electric Arc Protection Standard
- NFPA 70E-2012 Hazard / Risk Category HRC3
- ASTM 1959, ATPV 38 cal/cm²
- CAN/CGSB155.20-2000
- CAN/CGSB155.22-97, OSHA 29 CFR 1910.269
- CAN/CSA Z96-09 CLASS 1/LEVEL FR
- **Max Comfort™ 9 oz. 88% Cotton/12% Nylon FR twill fabric**
- **11.5 oz. modacrylic insulation / 3 oz. wind & vapor barrier**
- Two patch pockets on chest with snap closure
- Two-way concealed #10 – 2-way nomex FR brass break-away zipper
- Two front set-in hip pockets
- Two back patch pockets with concealed snap closures
- #10 nomex 28" FR zippers in vented legs with storm flap protection / snap closure
- Elasticized waist for comfort and security
- Sewn with FR Aramid thread
- All metal in garment is protected to avoid exposure to skin
- FR yellow-silver-yellow reflective tape: arms, legs, complete stripes on front
- FR yellow-silver-yellow reflective tape: X on back with complete belt
- Pen pocket on left sleeve

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved



MCR
SAFETY

DC5B FR Gear

Specification Sheet

APPLICATIONS:

Oil and Gas Industry, Electronic Assembly, Fracking, Mining,
Utilities

TECHNICAL DATA FOR: DC5B

Series	Max Comfort	Front Closure	YKK 2-Way Zipper & Triple
Category	FR Gear		Snap
Size	Large	NFPA 2112 Cert.	Yes
Material	Flame Resistant, 88% Cotton / 12% Nylon - Max Comf	NFPA 70E Cert.	Yes
Material Weight	9.0 oz.	OSHA 29 CFR 1910.269	Yes
Flame Resistant	Flame Resistant	CAN/CGSB 155.20-2000	Yes
		CAN/CGSB 155.22-97	Yes
		CAN-CSA Z96-09 CLASS 1/LE	Yes
		ASTM 1930 Cert.	Yes
		ASTM F1506 Cert.	Yes
		Hazard Risk Category	HRC3

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC5BS	36-38	N/A	N/A	30-32	N/A	N/A	41.890
DC5BLT	38 - 40	N/A	N/A	N/A	N/A	N/A	41.380
DC5BXL	42 - 44	N/A	N/A	N/A	N/A	N/A	33.700
DC5BX2T	46 - 48	N/A	N/A	N/A	N/A	N/A	41.890
DC5BX3T	50 - 52	N/A	N/A	N/A	N/A	N/A	35.540
DC5BX2	52-54	N/A	N/A	45-48	N/A	N/A	34.532
DC5BX4T	54 - 56	N/A	N/A	N/A	N/A	N/A	37.140
DC5BX3	56-58	N/A	N/A	51-54	N/A	N/A	35.860
DC5BX5T	58 - 60	N/A	N/A	N/A	N/A	N/A	41.890
DC5BX4	60-62	N/A	N/A	58-60	N/A	N/A	38.640
DC5BX5	64-66	N/A	N/A	62-64	N/A	N/A	38.372

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved