



**MCR  
SAFETY**

# H1N FR Gear

## Specification Sheet

### PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The H1 Henley Shirt features a 100% FR Cotton material for Maximum Comfort. The Max Comfort™ material meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Gray, Navy and Tan

### FEATURES:

- Max Comfort™ Fabric NFPA 2112 UL Certified
- All Trims are NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection Standard
- NFPA 70E HAZARD, HRC 2
- ATPV ASTM 1959 9.6 cal/cm<sup>2</sup>, HRC 2
- Henley is UL & NFPA 2112 CERTIFIED
- **Max Comfort™ 7.0 oz. 100% Cotton FR interlock knit shell**
- 3 button placket front
- Left chest pocket
- Fabric is moisture wicking and breathable
- Rib knit collar and cuff
- Hi-temperature FR poly buttons



### APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking, Mining

### TECHNICAL DATA FOR: H1N

<b>Series</b>	Max Comfort	<b>Front Closure</b>	Button
<b>Category</b>	FR Gear	<b>NFPA 2112 Cert.</b>	Yes
<b>Size</b>	Large	<b>NFPA 70E Cert.</b>	Yes
<b>Material</b>	Flame Resistant, 100% Cotton	<b>ASTM 1930 Cert.</b>	Yes

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: [www.mcrcsafety.com](http://www.mcrcsafety.com)

©2018 MCR Safety - All Rights Reserved



**MCR**  
SAFETY

# H1N FR Gear

## Specification Sheet

<b>Material Weight</b>	- Max Comfort 7.0 oz.	<b>ASTM F1506 Cert.</b>	Yes
<b>Flame Resistant</b>	Flame Resistant	<b>Hazard Risk Category</b>	HRC2

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
H1NS	34-36	N/A	N/A	N/A	N/A	N/A	29.484
H1NM	38-40	N/A	N/A	N/A	N/A	N/A	21.240
H1NL	42-44	N/A	N/A	N/A	N/A	N/A	32.580
H1NXL	46-48	N/A	N/A	N/A	N/A	N/A	34.416
H1NX2	50-52	N/A	N/A	N/A	N/A	N/A	36.504
H1NX3	54-56	N/A	N/A	N/A	N/A	N/A	38.304
H1NX4	58-60	N/A	N/A	N/A	N/A	N/A	39.852
H1NX5	62-64	N/A	N/A	N/A	N/A	N/A	41.544