



**MCR  
SAFETY**

# 96720NF

## Memphis

### Cut Protection Specification Sheet

#### **PRODUCT DESCRIPTION:**

Cool cut protection. Dyneema® is extremely cool to work in and offers the best abrasion resistance of the high performance fibers. The 96720NF features a 13 gauge Dyneema®/Synthetic shell with a nitrile foam coating on the Palm and Fingertips.

#### **FEATURES:**

- Breathable Dyneema® shell for maximum comfort
- Encourages workers to wear their gloves longer thereby reducing injuries
- Color coded hem sizing for easy identification
- Individually poly bagged by the pair and sold by the dozen

#### **APPLICATIONS:**

Automotive Assembly, Bottling, Canning, Glass handling, HVAC, Sheet metal industry



#### **TECHNICAL DATA FOR: 96720NF**

<b>Series</b>	Memphis	<b>EN 388 : CE Score - Abrasion</b>	4
<b>Material Group</b>	Strings	<b>EN 388 : CE Score - Cut</b>	3
<b>Product Type</b>	Cut Protection	<b>EN 388 : CE Score - Tear</b>	4
<b>Glove Size</b>	Large	<b>EN 388 : CE Score - Puncture</b>	3
<b>Gauge</b>	13 Gauge	<b>ANSI Cut</b>	ANSI Cut A3
<b>Material</b>	Dyneema	<b>ANSI Abrasion</b>	ANSI Abrasion 5
<b>Made In</b>	Sri Lanka		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: [www.mcrcsafety.com](http://www.mcrcsafety.com)

©2018 MCR Safety - All Rights Reserved



**MCR**  
SAFETY

# 96720NF

**Memphis**

**Cut Protection  
Specification Sheet**



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
96720NFXL	X - Large	13.79	4.13	3.35	32.160 lb.	2.680
96720NFS	Small	12.40	3.50	3.15	24.624 lb.	2.052
96720NFL	Large	13.39	3.94	3.35	29.916 lb.	2.493
96720NFM	Medium	12.80	3.74	3.15	28.284 lb.	2.357
96720NFXS	X - Small	11.80	3.35	2.95	22.680 lb.	1.890
96720NFXXL	XX - Large	14.18	4.33	3.35	33.780 lb.	2.815

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: [www.mcrcsafety.com](http://www.mcrcsafety.com)

©2018 MCR Safety - All Rights Reserved