



**MCR
SAFETY**

9672RE

Cut Protection Specification Sheet

PRODUCT DESCRIPTION:

DSM Dyneema® is a high modulus polyethylene (HMPE) fiber available as a continuous filament, spun or engineered fiber (yarn). DSM Dyneema® is 15 times stronger than surgical steel and features excellent abrasion resistance, cut resistance, and comfort. The 9672RE includes a 13 gauge, salt and pepper, filament yarn DSM Dyneema® blended shell with a polyurethane (PU) palm and forefinger coating. The water based PU reinforced thumb crotch and forefinger offers enhanced grip and extended wear.

FEATURES:

- 13 gauge Salt and Pepper DSM Dyneema®/Nylon/Spandex shell
- Gray PU palm and finger coating
- Black Water based PU reinforced thumb crotch and forefinger

APPLICATIONS:

Agriculture, Assembly Line Production, Carpentry, Construction, Demolition, Glass handling, Janitorial, Recycling, Roofing, Salvage, Warehousing



TECHNICAL DATA FOR: 9672RE

Material Group	Synthetic	EN 388 : CE Score - Abrasion	4
Product Type	Cut Protection	EN 388 : CE Score - Cut	3
Glove Size	Large	EN 388 : CE Score - Tear	4
Gauge	13 Gauge	EN 388 : CE Score - Puncture	1
Material	Dyneema	ANSI Cut	ANSI Cut A2
Thumb Style	Reinforced		
Made In	Sri Lanka		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved



MCR
SAFETY

9672RE

Cut Protection Specification Sheet



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
9672REL	Large	13.39	3.94	3.35	24.450 lb.	2.038
9672REXL	X - Large	13.79	4.13	3.35	22.880 lb.	1.907
9672REM	Medium	12.80	3.74	3.15	21.940 lb.	1.828
9672RES	Small	12.40	3.50	3.15	20.350 lb.	1.696

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2019 MCR Safety - All Rights Reserved