



**MCR
SAFETY**

9672RE

Cut Protection Specification Sheet

PRODUCT DESCRIPTION:

DSM Dyneema® is a high modulus polyethylene (HMPE) fiber available as a continuous filament, spun or engineered fiber (yarn). DSM Dyneema® is 15 times stronger than surgical steel and features excellent abrasion resistance, cut resistance, and comfort. The 9672RE includes a 13 gauge, salt and pepper, filament yarn DSM Dyneema® blended shell with a polyurethane (PU) palm and forefinger coating. The water based PU reinforced thumb crotch and forefinger offers enhanced grip and extended wear.

FEATURES:

- 13 gauge Salt and Pepper DSM Dyneema®/Nylon/Spandex shell
- Gray PU palm and finger coating
- Black Water based PU reinforced thumb crotch and forefinger

APPLICATIONS:

Agriculture, Assembly Line Production, Carpentry, Construction, Demolition, Glass handling, Janitorial, Recycling, Roofing, Salvage, Warehousing



TECHNICAL DATA FOR: 9672RE

Material Group	Synthetic	EN 388 : CE Score - Abrasion	4
Product Type	Cut Protection	EN 388 : CE Score - Cut	3
Glove Size	Large	EN 388 : CE Score - Tear	4
Gauge	13 Gauge	EN 388 : CE Score - Puncture	1
Material	Dyneema	ANSI Cut	ANSI Cut A2
Thumb Style	Reinforced		
Made In	Sri Lanka		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

9672RE

Cut Protection Specification Sheet



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
9672REXL	X - Large	13.79	4.13	3.35	22.880 lb.	1.907
9672REL	Large	13.39	3.94	3.35	24.450 lb.	2.038
9672REM	Medium	12.80	3.74	3.15	21.940 lb.	1.828
9672RES	Small	12.40	3.50	3.15	20.350 lb.	1.696