



**MCR
SAFETY**

9676 UltraTech Cut Protection Specification Sheet

PRODUCT DESCRIPTION:

One of the most distinguishing of DSM Dyneema® material is its cool-to-touch property. This fiber's inherent ability to dissipate body heat and pass moisture from inside of the glove to the outside, results in longer wear time which promotes greater hand protection. The 9676 features a 15 gauge DSM Certified Dyneema® Diamond Technology shell with PU coated palm and fingers. (Vending Packaged option available - VP9676).

FEATURES:

- 15 Gauge Dyneema® Diamond Technology Salt & Pepper Blended Shell
- Gray PU Coated Palm and Fingers
- Cool and Comfortable

APPLICATIONS:

Automotive Assembly, Farming, Landscaping, Carpentry, Glass handling, HVAC, Janitorial, Sheet metal industry, Roofing



TECHNICAL DATA FOR: 9676

Series	UltraTech	EN 388: CE Score - Abrasion	4
Material Group	Strings	EN 388 : CE Score - Cut	3
Product Type	Cut Protection	EN 388 : CE Score - Tear	4
Glove Size	Large	EN 388 : CE Score - Puncture	3
Gauge	13 Gauge	ANSI Cut	A3
Material	Dyneema	ANSI Puncture	3
		ANSI Abrasion	6
Made In	South Korea,Sri Lanka		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2020 MCR Safety - All Rights Reserved



MCR
SAFETY

9676

UltraTech

Cut Protection

Specification Sheet



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
9676XL	X - Large	12.60	4.13	2.95	23.592 lb.	1.966
9676XXL	XX - Large	12.98	4.33	2.95	25.656 lb.	2.138
9676XS	X - Small	10.63	3.35	2.56	17.628 lb.	1.469
9676S	Small	11.22	3.54	2.76	18.984 lb.	1.582
9676M	Medium	11.62	3.74	2.76	19.680 lb.	1.640
9676L	Large	12.20	3.94	2.95	21.900 lb.	1.825

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2020 MCR Safety - All Rights Reserved