



**MCR
SAFETY**

9696 UltraTech Dipped Specification Sheet

PRODUCT DESCRIPTION:

The NXG® series offers users with options that can increase tactile sensitivity, dexterity, and abrasion resistance. This series offers a variety of palm coatings over a durable nylon or poly / cotton shells to fit your needs. The 9696 features a 13 gauge gray nylon shell and gray polyurethane coating on the palm and fingertips. (Vending Packaged option available - VP9696). Offers good gripping power in wet or dry applications.

FEATURES:

- Great tactile sensitivity
- Excellent comfort and fit
- Excellent grip
- Greater dexterity
- Abrasion resistance

APPLICATIONS:

Aerospace, Assembly Line Production, Automotive Assembly, Carpentry, Janitorial , Landscaping



TECHNICAL DATA FOR: 9696

Series	UltraTech	EN 388: CE Score - Abrasion	4
Material Group	Strings	EN 388 : CE Score - Cut	1
Product Type	Dipped	EN 388 : CE Score - Tear	3
Glove Size	Large	EN 388 : CE Score - Puncture	1
Gauge	13 Gauge	ANSI Puncture	2
Material	Nylon	ANSI Abrasion	3
Made In	China,South Korea		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2020 MCR Safety - All Rights Reserved



MCR
SAFETY

9696
UltraTech
Dipped
Specification Sheet



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
9696XS	X - Small	11.535	3.425	2.677	10.032 lb.	0.836
9696XL	X - Large	13.072	4.134	2.835	13.260 lb.	1.105
9696XXL	XX - Large	13.504	4.173	2.874	12.204 lb.	1.017
9696L	Large	12.637	4.094	2.795	11.736 lb.	0.978
9696S	Small	11.811	3.543	2.677	11.352 lb.	0.946
9696M	Medium	12.205	3.740	2.756	11.388 lb.	0.949

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2020 MCR Safety - All Rights Reserved