



**MCR
SAFETY**

**9696
UltraTech
Dipped
Specification Sheet**

PRODUCT DESCRIPTION:

UltraTech® provides Ultra comfort, Ultra fit, and Ultra protection! The seamless nylon shell offers outstanding breathability and comfort while the Polyurethane palm and finger coating provides grip, puncture resistance, abrasion resistance and dexterity. Great for small parts handling. The 9696 features a 13 gauge gray nylon shell and gray polyurethane coating on the palm and fingertips. (Vending Packaged option available - VP9696).

FEATURES:

- Great tactile sensitivity
- Excellent comfort and fit
- Excellent grip
- Greater dexterity
- Abrasion resistance

APPLICATIONS:

Aerospace, Assembly Line Production, Automotive Assembly, Carpentry, Janitorial, Landscaping



TECHNICAL DATA FOR: 9696

Series	UltraTech	EN 388 : CE Score - Abrasion	4
Material Group	Strings	EN 388 : CE Score - Cut	1
Product Type	Dipped	EN 388 : CE Score - Tear	3
Glove Size	Large	EN 388 : CE Score - Puncture	1
Gauge	13 Gauge		
Material	Nylon		
Made In	Sri Lanka		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

9696
UltraTech
Dipped
Specification Sheet



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
9696XXL	XX - Large	13.504	4.173	2.874	13.584 lb.	1.132
9696S	Small	11.811	3.543	2.677	11.052 lb.	0.921
9696XL	X - Large	13.072	4.134	2.835	13.692 lb.	1.141
9696L	Large	12.637	4.094	2.795	12.504 lb.	1.042
9696XS	X - Small	11.535	3.425	2.677	10.956 lb.	0.913
9696M	Medium	12.205	3.740	2.756	12.216 lb.	1.018

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved