



**MCR
SAFETY**

N96790

Ninja

Dipped

Specification Sheet

PRODUCT DESCRIPTION:

MCR Safety Ninja® gloves are engineered to provide the highest level of innovation. Each of the offerings in the Ninja® series include a unique shell and polymer combination incorporating the latest in hand protection technology. Our Ninja® Glove Line offers the greatest assortment of dexterity, sense of touch, and protection. This Ninja® BNF (Breathable Nitrile Foam) with NFT® coating features a 15 gauge nylon/spandex shell that has a palm and fingertips coating. (Available in Vending Packaged Option - VPN96790).

FEATURES:

- 15 gauge nylon/spandex shell
- BNF (Breathable Nitrile Foam) with NFT® Coating on palm and fingertips
- Great dexterity, flexibility, and movement
- Ergonomic design for minimum hand fatigue
- Excellent wet or dry grip

APPLICATIONS:

Automotive Assembly, Farming, Landscaping, Manufacturing, Material Handling



TECHNICAL DATA FOR: N96790

Series	Ninja	EN 388: CE Score - Abrasion	4
Material Group	Strings	EN 388 : CE Score - Cut	1
Product Type	Dipped	EN 388 : CE Score - Tear	4
Glove Size	Large	EN 388 : CE Score - Puncture	1
Gauge	15 Gauge	ANSI Puncture	2
Material	Nylon	ANSI Abrasion	4
Made In	Pakistan,USA		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2020 MCR Safety - All Rights Reserved



MCR
SAFETY

N96790

Ninja

Dipped

Specification Sheet



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
N96790L	Large	10.039	3.74	2.756	17.580 lb.	1.465
N96790S	Small	9.055	3.543	2.559	13.836 lb.	1.153
N96790M	Medium	9.449	3.74	2.756	17.112 lb.	1.426
N96790XXL	XX - Large	10.827	3.937	3.071	20.436 lb.	1.703
N96790XL	X - Large	10.433	3.937	2.953	19.500 lb.	1.625
N96790XS	X - Small	8.661	3.346	2.559	14.700 lb.	1.225

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2020 MCR Safety - All Rights Reserved