



MATERIAL/PRODUCT SAFETY DATA SHEET

1. Identification of the Substance or Preparation and Company

1.1 Product : Lithium/Thionyl Chloride(Li/SOCl₂) Cells & Batteries

1.2 Model : TEKCELL (Brand name)

Which is named as SB-AA02, SB-AA11, SB-A01, SB-C02, SB-D02,
SW-AA11, SW-C01, SW-D02 and series of SB and SW.

1.3 Company

Name : Vitzrocell, Co. Ltd

Address : 256-41 Dugok-ri, Sinam-myon, Yesan-gun, ChungCheong Nam-Do

Tel : +82-41-332-8642~5

Fax : +82-41-332-8646

Website : www.vitzrocell.com

Details of the supplier of the safety data sheet

Supplier Address

MCR Safety 1255 W Schilling Blvd Collierville, TN 38017

1-800- 955-6887

Emergency Telephone Number

Company Phone Number

1-508-699-4406 Emergency Telephone (24 hr)

INFOTRAC 1-352-323-3500 (International)

2. Composition & Information on Ingredients

Ingredient	Content (%)	CAS No.
Lithium(Li)	3.0 ~ 4.5%	7439- 93- 2
Carbon (C)	3.0 ~ 4.5%	1333- 86- 4
Electrolyte(SOCl ₂)	30 ~ 45%	7719-09-7
Aluminium Chloride(AlCl ₃)	2.0 ~ 4.0%	7446-70-0

3. Hazards Identification

The lithium thionyl chloride batteries described in this MSDS are hermetically sealed unit, which are not hazardous when used according to the recommendations of the manufacturer.

Under normal condition of use of the batteries, the electrode materials and the liquid electrolyte they contained are non-reactive provided the battery integrity is maintained. Risk of exposure exists only in case of mechanical, electrical or thermal abuse. Thus, the batteries should not short circuit, recharge, puncture, incinerate, crush, immerse in water, force discharge, or expose to above the temperature range of the cell or battery. In these cases, there is risk of fire or explosion.



4. First Aid Measures

Handle according to emergency measures under in case of battery rupture, explosion or leakage and evacuate personnel from contaminated area and provide good ventilation to clear out corrosive fumes, gases or the pungent odour. Seek immediate medical attention.

Inhalation – Remove from exposure, rest and keep warm. In severe cases, obtain medical attention

Skin Contact – Wash off skin thoroughly with flow water for 10~15 minutes and obtain medical attention.

Eye Contact – Irrigate thoroughly with Water for at least 15 minutes and obtain medical attention.

Ingestion – Wash out mouth thoroughly with water and give plenty of water to drink for vomit and obtain medical attention.

5. Fire Fighting Measures

It is effective to use cold water in order to prevent spread of fire caused by lithium cells. However, never use hot water.

Lith-X(Class D extinguishing media) is the only effective on fires involving a few lithium batteries. If the cells are directly involved in a fire, DO NOT USE WATER, SAND, CO₂, HALON and DRY POWDER or SODA ASH EXTINGUISHERS.

If a fire is in adjacent area, and cells are packed in their original containers, the fire can be fought based on fuelling material, e.g. paper and plastic products.

6. Accidental Release Measures

Do not breathe vapours or touch liquid with bare hand. If the skin has come into contact with the electrolyte, take an action in accordance with 4. First Aid Measures.

Graphite powder should be used to absorb the exudation, seal leaking battery and graphite powder in plastic bag and dispose of Special Waste.



7. Handling and Storage

Handling – Prevent short circuit and do not use the battery above the temperature rating of battery. Do not recharge, force over-discharge (voltage below 0.0V), puncture and compress.

Storage – Storage preferably in cool (below 30°C) and non-elevated temperatures place. Storage in high temperatures can result in shortened battery life and degrade performance. Do not store batteries in high humidity, shock and vibration environments.

Others – Do not charge Li/SOCl₂ primary battery which is not chargeable battery. Follow manufacturer's recommendations regarding maximum recommended current and operating temperature range.

8. Exposure Controls & Personal Protection

The following safety measures are not necessary in normal use. They need only be applied if there is a risk that, in use or handling, the recommendations, as outlined in Section 3, have not been followed.

Respiratory protection – In all fire situations, use filter mask or self-contained breathing Apparatus for harmful gases or other material prevention.

Hand protection – In leakage situations, use specific gloves for leaking chemical substance and heat prevention.

Eye protection – Use safety goggles or face shield which can separate eyes and the outside for chemical substance and heat prevention.

Other protective equipment – Additional equipments are needed to prevent from chemical substance, harmful material and heat. (Clothes, boots etc.)

9. Physical and Chemical Properties

Appearance	Cylindrical shape
Odour	Odourless. If leaking, gives off a pungent and corrosive odour.
pH	Not applicable (Unless individual components exposed)



Boiling point	Not applicable (Unless individual components exposed)
Vapour pressure (mmHg,25°C)	Not applicable (Unless individual components exposed)
Relative density	Not applicable (Unless individual components exposed)
Flash point	Not applicable (Unless individual components exposed)
Flammability	Not applicable (Unless individual components exposed)
Solubility (water)	Not applicable (Unless individual components exposed)
Solubility (other)	Not applicable (Unless individual components exposed)
Physical state	Solid

10. Stability and Reactivity

Product is stable under conditions described in Section 7 (Handling and storage).

Conditions to avoid – heating and incineration above 90 °C, transformation, abscission, compression, puncture, disassembly, charge, a short circuit, storage in high humidity for a long time.

Material to avoid – Prevent to contact Oxidizer, Strong carbonated water, Alkali solutions, Water (H₂O), Aluminium, Zinc, and Electrolyte.

Harmful materials caused by disassembly

1. Water (H₂O) reacts with lithium metal to form powder such as lithium hydroxide (LiOH), lithium oxide and hydrogen gas (H₂)
2. In case of heating Thionyl chloride(SOCl₂) above 150 °C, chlorine(Cl₂), sulfur dioxide(SO₂), sulphur trioxide(SO₃), disulfur dichloride(S₂Cl₂), sulphur dichloride (SCl₂), lithium oxide(Li₂O) may occur.
3. Water (H₂O) reacts with thionyl chloride(SOCl₂) in room temperature to form hydrochloric acid(HCl) and sulphur dioxide(SO₂).



11. TOXICOLOGICAL INFORMATION

Symptoms and Signs – None, unless battery ruptures. In the event of exposure to internal contents, corrosive fumes will be very irritating to skin, eyes and mucous membranes.

Inhalation – Lung irritant.

Skin contact – Skin irritant

Eye contact – Eye irritant

Ingestion – if swallow, it can be poisoned.

Medical condition aggravated by exposure – In the event of exposure to internal contents, eczema, skin allergies, lung injuries, asthma and other respiratory disorders may occur.

12. Ecological Information

When properly used or disposed the battery does not present environmental hazard.

Cells of Vitzrocell do not contain mercury, cadmium, lead and Cr^{6+} which has a bad influence on environment.

13. Disposal Considerations

Do not incinerate or subject cells to temperatures in excess of 85°C . In the event of such abuse can result in loss of seal that causes explosion.


Cells should be separated after use in order to prevent short circuit terminal by using tape or other tools and dispose of in accordance with regulations.

14. Transportation

According to UN regulation, cells and batteries can be classified according to lithium content in unit cell or battery. The following <Table-1> is the classification of the lithium metal batteries(cells) by above provision and <Table-2> is the classification of Vitzrocell's batteries(cells)



<Table-1>



<Table-2>

Model	Li metal in cell(g)	D.C Class
SB-AA02	0.3	Section II
SB-AA11	0.62	section IB
		section II (less than 8cell)
SB-A01	0.97	section IB
		section II (less than 8cell)
SB-C02	2.18	section IA Class9
SB-D02	4.9	section IA Class9
SB-D02(Cap)	4.9	section IA Class9
SWH-DD01	8.3	section IA Class9
SC-DD01	7.16	section IA Class9
SW-AA11	0.66	section IB
		section II (less than 8cell)
SW-AA01	0.83	section IB
		section II (less than 8cell)
SW-C01	1.84	section IA Class9
SW-D02	4.5	section IA Class9



. Lithium cell must pass relevant examination regardless of lithium content. Relevant regulation and examination regulation for product are as follows.

- The UN Recommendations on the Transport of Dangerous Goods, Model Regulations
- The UN recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, Part III, Section 38.3

Hazard Classification: Class9

UN Number: 3090 Lithium batteries

3091 Lithium batteries contained in equipment or

Lithium batteries packed with equipment

Packing group: II

Other regulation and guideline

ADR, RID 188, 230, 310, P903

IATA A88, A99, A154, A164

IMDG code 188, 230, 310, P903

Lithium cell is restricted by transport through a passenger plane in case of air transport.

15. Regulatory Information

None

16. Other Information

TEKCELL (manufacturer: Vitzrocell) was recognized safety by UL (Underwriters Laboratories) located in Northbrook, U.S.A. (UL File No. : MH 18384)



Vitzrocell has all authorities about this MSDS. In case of use of relevant data by outside presentation, should get permission by Vitzrocel